

Drehmaschinen

SCHAUBLIN[®]
MACHINES SA

SCHAUBLIN 125CCNR-T

Machine occasion N° de stock : **DB3075**



CNC-Steuerung

Fanuc 20-T

Year

1997

Maximal zulässiger Durchmesser über den Wagen	115 mm
Maximal zulässiger Durchmesser über dem Bett	270 mm
Spitzenhöhe	125 mm
Spindelleistung	5.5/7.5 KW
Spindelgeschwindigkeit	30-5000 tr/min
Spindeldurchmesser	28 mm
Maximaler Drehdurchmesser	200 mm
Querverschiebung	150 mm
Längsbewegung	325 mm
Vorschubgeschwindigkeit	X/Z : 0-5 mm/mn
Schnelle Vorschübe X und Y	7500 m/mn
Anzahl der Revolver	1
Anzahl der Positionen auf Revolver 2	8
Kapazität des Behälters	55 Liters
Abmessungen	1697x1236x1658 mm
Weight	1415

Equipments:

- Oil mist vacuum cleaner Lufttechnik from 2004
- Pneumatic tailstock Mo3 operated with a pneumatic command, axial spindle stroke 70 mm. Adjustable pressure from 25 to 260 daN
- Marcel-Aubert Tool zero setting microscope
- Headstock (spindle) type D1-3
- Spindle nose adapter for OTTET collets
- RJ45 system for program backup
- Different B32 collets
- Drawbar with nuts for adaptation chucks from various makes and for HAINBUCH clamping
- Set of tool holders

Tooling system: Turret with fixed tools

- Set of tool holders
- Tool holder type VDI 20
- Maximum tool section 16x16 mm
- Integrated cooling system. Indexing in both directions





