

Механика



KENT KGS 1532D

Machine occasion N° de stock : **A3472-1**



Год

2006

Движение в длину

3200 мм

Перекрёстное движение	1700
Вертикальный ход	700 мм
Площадь панели	3200x1500 мм
Размеры абразивов	500x120x203,2 мм
Продвижение работы	5000 à 30000 мм/мин
Мотор патрона	32 лс
Размеры	11030x6075x4450 mm
Вес	32400 кг





3.2.0 Electrical connection

	27 1644	27 1643	27 1642
Connection code		98	
Connection ratio		63 mm ²	
Supply voltage		400 V 3 phase - 50 Hz - 3N+X	
Control voltage		24 V 0	
Magnetic flux density		1000 mm ² in total 200 V 10 A max	
Insulation resistance		500 VAC 1 MΩ between connection terminal and ground	
Operating temperature		0 °C to 30 °C	

3.3.0 Lubricants and operating fluids

3.3.1 Hydraulic unit

Tank capacity: 1000 litres

Lubricant grade: ADDONEL HLP 68, 68P Energol HLP 68/68
 Castrol HYPOL AVIS 68, CHEVRON RIVOLTO HD 68, Esso Nuto H 68, GM HY-PHM 68, SHELL Tellus 68, Mobil DTE 68 or lubricants from different manufacturers that possess the same properties.

3.3.2 Lubricant tank

Tank capacity for 8 axes: 120 litres

Lubricant grade: CFC - Solimex 68, KISOOL - Fuchs AGS, MOBIL - Virex 24 No. 2, SHELL - Turbis 700 or lubricants from different manufacturers that possess the same properties.

Tank capacity for 7 and 2 axes: 400 litres

1 grease cartridge brand Mobilux GP-C.

3.3.3 Coolant tank

Tank capacity: 1700 litres

The tank is filled with water and coolant solution in the ratio the operator's.



